



INTERFACES - INTELLIGENT

SOTERIA® DIN RAIL INPUT/OUTPUT UNIT



DIN RAIL
INPUT/OUTPUT UNIT
AP-SADIN-IO

DESCRIPTION

The Soteria® DIN Rail Input/Output Unit supervises of one or more normally open volt-free contacts connected to a single pair of cables and a set of changeover relay output contacts.

The I/O unit is designed to be mounted on a 35 mm-width DIN Rail inside an enclosure.

The Soteria DIN Rail Input/Output Unit complies with the essential requirements of the EMC Directive 2014/30/EU, as well as the Construction Products Regulation 305/2011.

FEATURES

- Improved design for ease of wiring facilitates faster installation
- Contains controllable isolator*
- Address range 1-254*
- Nine pre-configured modes, including compatibility mode from XP95/Discovery to CoreProtocol® systems*
- Failsafe mode compliant to BS 7273-4 requirements
- Configurable input styles*
- Earth fault monitoring*

Note: *CoreProtocol® enabled systems feature only.

Please check with Technoswitch for availability.

APPROVALS

- EN54-17, EN54-18 (Incl. Vibration, Impact & Shock)
- CPR
- LPCB



INTERFACES - INTELLIGENT

SOTERIA® DIN RAIL INPUT/OUTPUT UNIT

SPECIFICATIONS

DIN RAIL INPUT/OUTPUT UNIT - AP-SADIN-IO

Supply Voltage	17-35 V DC
Protocol	5-13 V peak to peak
Power-up Surge Current	900 μ A
Quiescent Current	500 μ A
Max Current	
LEDs On	3.5 mA
LEDs Disabled	500 μ A
Relay Output Contact Rating	1 A at 30 V DC or AC
Operating Temperature	-40 °C to +70 °C
Humidity	0 % to 95 % RH (no condensation or icing)
Dimensions H x W x D	33 x 102 x 33 mm
Weight	49 g

* Specifications are typical at 24 V, +25 °C, and 50 % RH, unless otherwise stated.

ORDERING INFORMATION

Product Code	Product Description
AP-SADIN-IO	SOTERIA®/XP95 Intelligent DIN Rail Input/Output Unit
AP-SAI-IO	SOTERIA®/XP95 Intelligent Input/Output Unit
AP-SAI-IO2	SOTERIA®/XP95 Intelligent Dual Input/Output Unit
AP-SAI-SM	SOTERIA®/XP95 Intelligent Switch Monitor
AP-SAI-SM2	SOTERIA®/XP95 Intelligent Dual Switch Monitor
AP-SAI-MSIO	SOTERIA®/XP95 Intelligent Mains Switching Input/Output Unit
AP-SADIN-MSIO	SOTERIA®/XP95 Intelligent DIN Mains Switching Input/Output Unit
AP-SADIN-SM	SOTERIA®/XP95 Intelligent DIN Rail Switch Monitor

• **DISCLAIMER:** Although the contents of our product literature have been prepared with the greatest care, Technoswitch can accept no liability whatsoever for any direct or indirect damages of any kind that may arise due to either errors or omissions in them, or amendments to products or other specifications following publication.

© Technoswitch Fire Detection (Pty) Ltd